

DIMENSIONS		CFT100	CFT115	CFT130	CFT160	CFT180	CFT200	CFT230	CFT260
Width	mm	1110	1110	1110	1110	1110	1110	2210	2210
Length	mm	3050	3050	3050	4050	4050	4050	3050	3050
Height	mm	1950	1950	1950	1950	1950	1950	1950	1950
Weight	Kg								

COMPONENTS DESCRIPTION		CFT100	CFT115	CFT130	CFT160	CFT180	CFT200	CFT230	CFT260
Refrigerant type		R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Compressor		Bitzer	Bitzer	Bitzer	Bitzer	Bitzer	Bitzer	Bitzer	Bitzer
Compressor type		Scroll	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll
N° circuits/compressors		1/2	1/2	1/2	1/2	1/2	1/2	2/4	2/4
Evaporator		Brazed plates	Brazed plates	Brazed plates	Brazed plates	Brazed plates	Brazed plates	Brazed plates	Brazed plates
Condensator		Aluminium micro-channel	Aluminium micro-channel	Aluminium micro-channel	Aluminium micro-channel	Aluminium micro-channel	Aluminium micro-channel	Aluminium micro-channel	Aluminium micro-channel
Expansion device		Expansion valve	Expansion valve	Expansion valve	Expansion valve	Expansion valve	Expansion valve	Expansion valve	Expansion valve
Solenoid valve on liquid refrigerant line		STD	STD	STD	STD	STD	STD	STD	STD
Refrigerant gauge		STD	STD	STD	STD	STD	STD	STD	STD
Low pressure switch		STD	STD	STD	STD	STD	STD	STD	STD
Fan type		Axial	Axial	Axial	Axial	Axial	Axial	Axial	Axial
Water differential pressure switch		STD	STD	STD	STD	STD	STD	STD	STD
Inlet water temperature probe		STD	STD	STD	STD	STD	STD	STD	STD
Outlet water temperature probe		STD	STD	STD	STD	STD	STD	STD	STD
Inlet water filter in the evaporator		STD	STD	STD	STD	STD	STD	STD	STD
Controller type		Microprocessor	Microprocessor	Microprocessor	Microprocessor	Microprocessor	Microprocessor	Microprocessor	Microprocessor
Compressors Crankcase Resistors		STD	STD	STD	STD	STD	STD	STD	STD
Phase sequence control relay switch		STD	STD	STD	STD	STD	STD	STD	STD
RS485 interface		STD	STD	STD	STD	STD	STD	STD	STD
IP protection degree		IP54	IP54	IP54	IP54	IP54	IP54	IP54	IP54

OPTIONS AVAILABLE									
Single P2 Pump	P2								
Single P3 Pump	P3								
Double P2 Pump	D2								
Double P3 Pump	D3								
Non ferrous water piping for single pump units	WP [1]								
Non ferrous water piping for double pump units	WD [2]								
Pressurized Water Tank	TP								
Non ferrous pressurized water circuit (AISI304 stainless steel water tank)	TPI								
Shut-off compressor valve	VSC								
Water Level Switch	LS								
Evaporator anti freeze heater	RA1								
Evaporator and pump anti freeze heater	RA2								
Evaporator, pump and tank anti freeze heater	RA3								
Electrical Switchboard anti-condensation Resistor	RS								
Automatic Water Filling Kit	WF								
Water Double Set point	WE								
Condensing Control: Electronic fans	CE								
Condenser with e-coating protection	OEC								

FACTORY MOUNTED ACCESSORIES									
Condenser air filters	FP								
Packing with barrier bag	PBB								
Container loading	PCL								
Wooden Basement	PWB								
Wooden Crate	PWC								N/A

ACCESSORIES SUPPLIED SEPARATELY									Net price
Flanged Water Connections (EN1092-1)	WC1								
Threaded Water Connections (GAS)	WC2								
Rubber anti-vibration mountings for no tank units	FA1								
Rubber anti-vibration mountings for units with tank	FA2								
Remote Panel	ER								

[1] WP option provides EPDM piping and AISI304 stainless steel connections. Combine WP with an option P2,P3 but it's not available with TP, TPI,

[2] To combine with an option P2,P3.